

THOMPSON TRACTOR: BACK IN ACTION, READY TO SERVE YOU IN FORESTRY AGAIN!



THOMPSON FORESTRY



B458 TRACK FELLER BUNCHER

POWERTRAIN

Cat C9.3 engine certified to EPA Tier 4 Final
Primary, secondary, and tertiary fuel filters, including water separator
Side-by-side radiator and oil cooler
Swing out air-to-air cooler and air conditioner condenser
Removable debris screen
Centrifugal engine air pre-cleaner
Under-hood 2-stage engine air cleaner
Variable pitch, reversing fan with guard
Heavy-duty starter and ether aid

UNDERCARRIAGE

Three-cylinder leveling system
Heavy-duty variable gauge track roller frames
Grease-lubricated 336 HD HEX track
Straddle mounted carrier rollers
Heavy-duty bottom track rollers
Heavy-duty recoil mechanisms
Full length track shoe support
Heavy-duty travel motor and swivel guards
Towing eyes on base frame

HYDRAULICS

One hydraulic pump group for implement functions
One hydraulic pump group for track functions
Dedicated attachment pump for head functions
Dedicated saw pump
High-performance hydraulic return filters
325 size, high torque swing drive
Swing cushion valve and automatic swing parking brake
Electric hydraulic oil fill pump
Spare hose storage area

ELECTRICAL

1115 ampere alternator 24-volt electrical system with 2
12-volt batteries
9 LED working lights and 2 LED service lights
Horn and travel alarm
Secondary engine shut off switch
Product Link™ ready

SALES AND SERVICE

Sold and serviced exclusively through Weiler Forestry
dealers worldwide

OPERATOR ENVIRONMENT

Enclosed FOPS/ROPS/OPS/OR-OSHA/WCB certified cab
Air suspension with integrated joysticks and head rest
Left-hand tilt console
Retractable 4-point seat belt
Touchscreen display monitor and programmable
operator controls
Scratch resistant polycarbonate windows
Reverse slope 1.25" (32 mm) front windshield
Front window emergency escape
Skylight Left-side fresh air window
Pressurized cab with filtered ventilation
Heater / air conditioner / defroster
Radio ready with speakers
Mount locations for CB radio and other accessories
Behind seat storage tray
Three cup holders, two USB sockets, and literature holder

OTHER STANDARD EQUIPMENT

Heavy-duty hood enclosure
Heavy-duty counterweight with machine level engine
enclosure access
Heavy-duty doors, covers, and bottom guards

OPTIONAL EQUIPMENT

Standard feller buncher boom and stick
Intermittent saw boom and stick
Boom and stick omission
30 or 50 mm counterweight
Standard or extended roller frames (eleven bottom rollers)
Standard or star carrier rollers
24" (600 mm) SG 336 HD HEX Track
28" (710 mm) SG or DG 336 HD HEX Track
Std. or deluxe cab (heated-cooled seat / satellite radio /
sun screens)
Standard deluxe lights (14 LED working lights)
Standard, cold, or arctic starting aid
201 continuous saw w/ partial or full tilt - 22.5" (572 mm)

WARRANTY

12 months standard, extended warranty available

SPECIFICATIONS

Engine Model	Cat® C9.3 Tier 4 Final	
Tractive Effort	81,229 lbf	36,845 kgf
Fuel Tank Capacity	216 gal	819 L
Gross Power	298 hp	222 kW
Undercarriage Size	336 HD HEX	
Engine Oil Capacity	10.6 gal	40 L
Engine Displacement	568 in ³	9.3 L
Undercarriage Pitch	8.5"	216 mm
Hydraulic System Capacity	79.8 gal	302 L
Weight (no head)	79,221 lb	35,934 kg
Ground Clearance	35"	881 mm
Transport Width	11' 11"	3.62 m
Maximum Flow	322 gpm	1220 L/min
Track Gauge	114"	2883 mm
Height	12' 11"	3.94 m
Max. Reach (w/ 201 saw)	26' 10"	8.19 m
Track Length	191"	4856 mm
Length (boom ext., w/201 saw)	34' 1"	10.39 m
Lift at Max. Reach (no head)	13,918 lb	6313 kg
Leveling System Capability	21° Forward 11° Side-to-Side	
Length (boom tuck., no head)	25' 7"	7.81 m

Base configuration includes standard feller buncher boom and stick, roller frames in the wide position, and 28" (710 mm) single grouser shoes.

Thompson

thompsontractor.com
833-681-7222

Materials and specifications are subject to change without notice. Featured machines and photos may include optional equipment. All rights reserved.