

THOMPSON TRACTOR: BACK IN ACTION, READY TO SERVE YOU IN FORESTRY AGAIN!



THOMPSON FORESTRY



K261 STATIONARY KNUCKLEBOOM LOADER

CONFIGURATIONS

1. On Board Electric Power w/
Operator's Cab on loader with pilot
joystick controls
2. On Board Electric Power w/
Remote Operator's Station with electric over
hydraulic controls
3. Remote Electric Power w/
Remote Operator's Station with electric over
hydraulic controls

NOTE: It is the customer's responsibility to provide the remote operator's station for configurations 2 & 3.

MOTOR POWER SUPPLY

75 hp (56 kW) @ 1800 rpm electric motor
380 Volt / 50 Hz Electric Power Supply option
460 Volt / 60 Hz Electric Power Supply option
575 Volt / 60 Hz Electric Power Supply option
Four ring high voltage / auxiliary low voltage
collector ring
NEMA 12 enclosure service panel
Direct pump drive through flex coupling
Magnetic starting system

HYDRAULICS

Three in-line gear pumps
44-33-22 gpm (167-125-83 L/min) of flow
Radial piston swing motor
80 gal (300 L) hydraulic reservoir

SALES AND SERVICE

Sold and serviced exclusively through Weiler Forestry
dealers worldwide

MOUNTING KITS

Steel Platform (includes mounting bolts, lock nuts,
washers, shock pads)
Concrete Pad (includes J-hook bolts, lock nuts,
washers, shock pads)
Optional 30" (762 mm) Subframe Riser for
concrete installations

NOTE: Steel platform and/or concrete pad design are the responsibility of the customer.

BOOM OPTIONS

25' (7.6 m) Standard Boom and Stick
27' (8.2 m) Standard Boom and Stick
30' (9.1 m) Standard Boom and Stick
30' 6" (9.3 m) Live Heel Boom and Stick

OPERATOR CAB - OPTIONAL

Right side mounted enclosed cab
Pressurized with heat and air conditioning
Adjustable seat with arm rests
Dual pilot joystick controls with foot pedal swing
Reverse slope tinted windshield
Windshield wiper
Lexan skylight
AM/FM radio
Sunshade

OPTIONAL EQUIPMENT

4042 Straight Narrow Jaw Grapple, R25 rotator
4548 Straight Narrow Jaw Grapple, R50 rotator
4548 Tapered Wedge Jaw Grapple, R50 rotator
Single "V" Heel Double "V" Heel
Boom Work Lights
Boom Central Grease Location
Hydraulic Tank Heater
Counterweight

WARRANTY

12 months standard

SPECIFICATIONS

Gross Power	75 hp	56 kW
System Pressure	2200 psi	152 bar
Electric Motor Options	380 Volt / 50 Hz 460 Volt / 60 Hz 575 Volt / 60 Hz	
Swing Pressure	2400 psi	165 bar
Swing Speed	8 rpm	
Swing Bearing Diameter (O.D.)	43"	1092 mm
Weight*	15,915 lb	7219 kg
Hydraulic Reservoir	80 gal	300 L

**Weight includes on board electric power, 25' boom, extended V heel and 4042 SN grapple*

Thompson 

thompsontractor.com

833-681-7222

Materials and specifications are subject to change without notice. Featured machines and photos may include optional equipment. All rights reserved.