

# THOMPSON TRACTOR: BACK IN ACTION, READY TO SERVE YOU IN FORESTRY AGAIN!

THOMPSON FORESTRY

## WEILER K562 KNUCKLEBOOM LOADER

### POWERTRAIN

Cat® C4.4 engine certified to EPA Stage 5  
Primary and secondary fuel filters, including  
water separator  
Electric fuel priming and transfer pump  
2-Stage engine air cleaner  
Oversized cooling system Engine auto idle down

### OPERATOR ENVIRONMENT

Enclosed cab with swing out front window guard  
meeting SAE J2267  
Steel console  
Dual pilot joystick control with foot pedal swing  
Reverse slope tinted windshield and skylight with sunshade  
Two cup holders  
High capacity HVAC system  
Air suspension high back seat  
AM/FM/Bluetooth Radio with 1 x USB port  
24V to 12V converter, 1 x 12V power port, and 2 x USB ports  
Windshield wiper All down stabilizer controls  
Stabilizer movement, pilot arming, and propel alarm  
Integrated carrier controls with foot propel pedal  
Weiler programming system  
Adjustable operator controls  
Backup camera with 10" screen  
24V to 12V converter and two 12V power ports

### ELECTRICAL

100 ampere alternator  
24-volt electrical system with 2 x 12-volt batteries  
Main disconnect switch with Diesel Exhaust Fluid (DEF)  
purge indicator light  
6 halogen working lights & 1 engine compartment  
service light  
20 circuit electric swivel

### SALES AND SERVICE

Sold and serviced exclusively through Weiler Forestry  
dealers worldwide

### HYDRAULICS

Weiler software monitors performance and delivers  
power where needed  
Load-sense hydraulics  
Variable displacement pumps  
Closed loop attachment system with 71 gallons of  
total oil volume

113 gpm (428 lpm) at 6,000 psi (41,369 kPa)  
attachment pump

High performance, multi-functioning main control valve  
Two dedicated hydraulic coolers  
Long life, in-tank hydraulic filter  
Electric hydraulic oil fill pump

### OTHER STANDARD EQUIPMENT

Extreme-duty boom and stick  
Heavy-duty, extended length center mount sub-frame  
Flat top sub-frame deck with bolt-on skid resistant fenders  
Bolt-on sub-frame ladder  
r12" (305 mm) grapple mounting knuckle

### OPTIONAL EQUIPMENT

Circle Saw Slasher Ready Hydraulics  
32' 6" Boom & Stick (9.9 m)  
32' 6" Live Heel Boom & Stick (9.9 m)  
36' Boom & Stick (11.1 m)  
Extended Single "V" or Double "V" Heels  
4548 Straight Narrow Jaw Grapple (2 Port Swivel)  
4548 Tapered Wedge Jaw Grapple (2 Port Swivel)  
5055 Straight Narrow Jaw Grapple (2 Port Swivel)  
5055 Tapered Wedge Jaw Grapple (2 Port Swivel)  
Premium Heated & Cooled Seat  
30" Fold-over Cab Riser (762 mm)  
LED Working Lights  
CB Radio  
Product Link (PL243 Cellular or PL631 Satellite)  
Two Additional Batteries  
Arctic Preheater  
Auxiliary Hydraulic Cooler  
Additional Ladders  
Vacuum Pump  
Bar Saw Slasher Hydraulics  
Bar Saw Slasher Hydraulics Adapters (JIC to ORFS)  
Bar Saw Slasher Hydraulics Adapters w/Shut Off Valves  
(JIC to ORFS)  
Fire Extinguisher

### WARRANTY

12 months standard, extended warranty available

## SPECIFICATIONS

Engine	ModelCat® C4.4 Stage 5	
Fuel Capacity	80.0 gal	303 L
Maximum Reach	32'	0"
Gross power	184 hp	137 kW
DEF Capacity	5.0 gal	19 L
Transport Width	8' 6"	2.57 m
Engine Speed	1800 rpm	
Swing Torque	49,173 lbf-ft	66 870 N·m
Transport Height	13' 3"	4.04 m
Weight	33,800 lb	15 331 kg
Swing Speed	11 rpm	
Transport Length	43'	13.11 m

Base configuration includes standard loader hydraulics and standard boom and stick. All transportation dimensions are of 43' self propelled trailer. Transport dimensions will vary with each carrier manufacturer.

**Thompson** **CAT**

thompsontractor.com  
833-681-7222

Materials and specifications are subject to change without notice. Featured machines and photos may include optional equipment. All rights reserved.