

THOMPSON TRACTOR: BACK IN ACTION, READY TO SERVE YOU IN FORESTRY AGAIN!

THOMPSON FORESTRY
WEILER S240 WHEEL SKIDDER



POWERTRAIN

Cat C7.1 engine certified to EPA Stage 5
Primary and secondary fuel filters, including water separator
Electric fuel priming pump
Electric fuel transfer pump
Centrifugal engine air pre-cleaner
2-Stage engine air cleaner
Front mounted cooling package
Engine driven fan
Variable speed hydrostatic ground drive
HD axles, approved for dual tires up to 30.5L-32 with 24.5L-32 and wide tires up to 73x44 with chains
Rear only differential lock
Lubed for life universal joints and HD drive shafts
Enclosed disc service brakes
Enclosed parking brake - spring applied, hydraulically released

HYDRAULICS

Load-sense hydraulics
Variable displacement pumps
High performance, multi-functioning main control valve
Spin on filters

OPERATOR ENVIRONMENT

Wide enclosed cab
Joystick steering with front foot controls
High capacity HVAC system
Air suspension seat with harness seat belt
AM/FM/Bluetooth Radio
24V to 12V converter, 12V power port, and 2xUSB ports
4 LED cab lights
Weiler programming system

ELECTRICAL

115 ampere alternator
24-volt electrical system with 2 x 12-volt batteries
Main disconnect switch with Diesel Exhaust Fluid (DEF) purge indicator light
Product Link™ Ready

SALES AND SERVICE

Sold and serviced exclusively through Weiler Forestry dealers worldwide

OTHER STANDARD EQUIPMENT

Heavy-duty frames
Narrow engine enclosure with high front visibility
Single side engine service
Dual tapered roller bearing upper and lower center hitch
Heavy-duty limb risers
Wide water tank ready decking blade with welded on cutting edge
Tilt Cab
Hand pump for hydraulic oil fill

OPTIONAL EQUIPMENT

Dual Function Arch/Boom and Grapple Head
Cable Arch and Extreme Duty Fenders
Industrial Arrangement
HD Box Section or Biomass Plate Grapple Tongs
No Winch, Winch Ready, Standard Winch, or High Speed Winch
Grapple Fenders
Wheel Steering
High Rotation Joystick Seat w/Added Rear Foot Controls
Additional LED Cab Lights (9 or 12 Total Lights)
Decking blade w/Bolt-on Cutting Edges
Pressurized Blade Mounted Water Tank
Ether Starting Aid
Electric Hydraulic Oil Fill Pump
CB Radio
Product Link™ (PL243 Cellular or PL631 Satellite)
7/8" x 75' Winch Cable w/7 Ton Hook
5 LB Fire Extinguisher
Water Tank Fill w/RV Antifreeze
30.5L-32 NOAW Tires - 126.6" (3220 mm)
30.5L-32 Tires - 133.3" (3390 mm), Approved for Chains
30.5L-32 2X Ring Tires - 126.6" (3220 mm)
35.5L-32 NOAW Tires - 139.1" (3530 mm)
35.5L-32 Tires - 145.8" (3700 mm), Approved for Chains

WARRANTY

12 months standard, extended warranty available

SPECIFICATIONS

ENGINE MODEL	Cat® C7.1 Stage 5	
WHEELBASE	144"	3652 mm
GROUND CLEARANCE	21.7"	550 mm
GROSS POWER	203 hp	151 kW
WEIGHT	41,000 lb	18 597 kg
BOX GRAPPLE CAPACITY	14.4 ft ²	1.34 m ²
ENGINE SPEED	2200 rpm	
TRANSPORT WIDTH	10' 7"	3.21 m
BOX GRAPPLE OPENING	126.2"	3205 mm
FUEL CAPACITY	83.2 gal	315 L
TRANSPORT HEIGHT	11' 1"	3.39 m
BIOMASS GRAPPLE CAPACITY	16.0 ft ²	1.46 m ²
DEF CAPACITY	5.0 gal	19 L
TRANSPORT LENGTH	27' 4"	8.32 m
BIOMASS GRAPPLE OPENING	136.3"	3462 mm

Base configuration includes 30.5L-32 26PR NOAW Tires, Fenders, Winch, Water Tank, Box Grapple, and Wide Blade. Weight add 545 lb (247 kg) 30.5L-32 2X Ring tires, 1,508 lb (684 kg) for 35.5L-32 tires. Height and ground clearance add 2.4" (61 mm) for 35.5L-32 tires.

Thompson 

thompsontractor.com
833-681-7222

Materials and specifications are subject to change without notice. Featured machines and photos may include optional equipment. All rights reserved.