

THOMPSON TRACTOR: BACK IN ACTION, READY TO SERVE YOU IN FORESTRY AGAIN!

THOMPSON FORESTRY
WEILER S250 WHEEL SKIDDER

POWERTRAIN

Cat C7.1 engine certified to EPA Tier 4 Final
Primary and secondary fuel filters, including water separator
Electric fuel priming pump
Electric fuel transfer pump
Centrifugal engine air pre-cleaner
2-Stage engine air cleaner
Cross-flow cooling system with swing out cores
Swing out air conditioner condenser and fuel cooler
Hydraulically driven, on demand reversing cooling fan
Powershift transmission with lock-up torque converter
Cat HD axles, approved for odd size dual tires up to 30.5L-32 with 24.5L-32 and wide tires up to 73-44 with chains
Independent front and rear differential locks
Lubed for life universal joints and HD drive shafts
Enclosed disc service brakes
Spring applied, hydraulically released parking brake

HYDRAULICS

Load-sense hydraulics
Variable displacement pumps
High performance, multi-functioning main control valve
In-tank return filter

OPERATOR ENVIRONMENT

Enclosed cab with swing out front window guard meeting SAE J2267
Dual pilot joystick control with foot pedal swing
Reverse slope tinted windshield and skylight with sunshade
Two cup holders
High capacity HVAC system
Air suspension high back seat
AM/FM/Bluetooth Radio
24V to 12V converter and 2 x 12V power port
Windshield wiper
All down stabilizer controls
Integrated trailer hydraulic landing gear control
Weiler machine software
Adjustable operator controls

ELECTRICAL

1115 ampere alternator
24-volt electrical system with 2 12-volt batteries
Main disconnect switch with Diesel Exhaust Fluid (DEF) purge indicator light
Jump start posts
Product Link™ Ready

SALES AND SERVICE

Sold and serviced exclusively through Weiler Forestry dealers worldwide

OTHER STANDARD EQUIPMENT

Heavy-duty frames
Dual tapered roller bearing upper and lower center hitch
Heavy-duty limb risers
Wide blade
Ecology drains (engine oil, engine coolant, hyd tank, axles, transmission)
Tilt Cab
Segregated engine/CEM and cooling compartments
Single side engine service
S-O-S sampling ports

OPTIONAL EQUIPMENT

Dual function arch/boom and grapple head
Cable arch and extreme duty fenders
Industrial arrangement
HD Box Section or Biomass Plate Grapple Tongs
Winch Ready, Retrieval Winch or Logging Winch
Grapple Fenders
Standard or Deluxe Cab
Wheel or Joystick Steering
Standard, Deluxe or Premium Working Lights
Window Screens
Pressurized Water Tank
30.5L-32 NOAW Tires - 126.6" (3216 mm)
30.5L-32 Tires - 133.3" (3386 mm), Approved for Chains
30.5L-32 2X Ring Tires - 126.6" (3216 mm)
35.5L-32 NOAW Tires - 139.1" (3533 mm)
35.5L-32 Tires - 145.8" (3703 mm), Approved for Chains
Ether Starting Aid
Electric Hydraulic Oil Fill Pump
Front and Rear Window Wipers
Secondary Steering

WARRANTY

12 months standard, extended warranty available

SPECIFICATIONS

Engine Model	Cat® C7.1 Tier 4 Final	
Wheelbase	143.8"	3652 mm
Ground Clearance	21.7"	550 mm
Gross power	203 hp	151 kW
Weight	45,357 lb	20,573 kg
HD Box Grapple Capacity	14.4 ft ²	1.34 m ²
Engine Speed	2200 rpm	
Transport Width	10' 7"	3.21 m
HD Box Grapple Opening	126.2"	3205 mm
Fuel Capacity	83.2 gal	315 L
Transport Height	11' 1"	3.39 m
Biomass Grapple Capacity	15.7 ft ²	1.46 m ²
DEF Capacity	5.0 gal	19 L
Transport Length	27' 4"	8.32 m
Biomass Grapple Opening	136.3"	3462 mm

Base configuration includes DF Grapple, 30.5L-32 26PR NOAW Tires, Fenders, Winch, Water Tank and Wide Blade. Weight add 545 lb (247 kg) 30.5L-32 2X Ring tires, 1,508 lb (684 kg) for 35.5L-32 tires. Height and ground clearance add 2.4" (61 mm) for 35.5L-32 tires.

Thompson **CAT**

thompsontractor.com
833-681-7222

Materials and specifications are subject to change without notice. Featured machines and photos may include optional equipment. All rights reserved.